Calculation for Constructed Wetland Storage Capacity Project Name: MSD Reviewer:_____ Date Submitted: WM No._____ Property Address:_____ Development/Property Name: GMP Number:_____ Design Firm:____ Design Engineer: _____ Telephone: ____ Email: _____ KY PE No.:____ Step A. Site Planning Recommendation Define goals and primary function of constructed wetlands based on the Constructed Wetlands fact sheet in section 18.4.2. Refer to this section as needed throughout the remainder of this calculation sheet. Step B. Calculate the Water Quality Volume Required (VR) of water to be removed by the Constructed Wetland ft^2 1. A = Contributing drainage area to constructed wetland: inches 2. RE = Required Water Quality Volume Rain Event in inches (minimum 0.6 in): % 3. I = Impervious cover of the contribution drainage area in percent: ft^3 4. VR = (1/12)(RE)(A)(0.05+(0.009)(I)) =Step C. Calculate the Water Quality Volume Provided (VP), or storage capacity of Constructed Wetland 1. PD = Volume of Pretreatment Device ft^2 2. A = Area of constructed wetland:40 3. p = porosity of media (% void):4. M = depth of mediaft 5. P = ponding depth of water6. VP = (A)[(p)(M) + P] + PDStep D. Prepare exhibits A and B for long-term maintenance and operation agreement.